

Laads

NLA2



Flat wagon unit with straight floor and scotch blocks
 Flachwageneinheit mit geradem Fußboden und Radvorlegern

	A	B	C	D	
S	37,5 t	45,5 t	53,5 t	53,5 t	**
120	00,0 t				

Gauge Profil	G1
Type of brake block LL-brake block, cast-iron (GG) brake block Sohlenart LL-Sohle (low noise, low friction), GG-Sohle (Grauguss)	LL/GG
Overall length over buffers Wagenlänge über Puffer	29.680 mm
Loading length Ladelänge	28.480 mm
Loading length horizontally Ladelänge horizontal	28.480 mm
Loading width Ladebreite	2.950 mm
Loading width between fixing rail/loading edge Ladebreite zwischen Radvorleger-Schienen/Ladekante	2.950 mm

Tare weight Eigengewicht	ca. 26.500 kg
Floor height above top of rail Fußbodenhöhe über Schienenoberkante	1.200 mm
Minimum curve radius Kleinster befahrbarer Gleisbogenhalbmesser	75 m
Guardrail Absturzsicherung	yes
Extra information per half wagon Zusatzdaten je Wagenhälfte	
Number of scotch blocks Anzahl Radvorleger	16 units
Load capacity Tragfähigkeit	ca. 26,75 t

